



SEALED LICENSE PLATE FRAMES

Thank you for choosing this fine product from GRIOT'S GARAGE. The **SEALED LICENSE PLATE FRAME** is made from durable, UV protected polycarbonate with a crystal clear lens. A flexible rubber gasket fits snugly around the plate to prevent moisture and dirt from getting inside. Snap-in fastener covers conceal the screw heads and give a sleek finished look. Enjoy the best.

USEFUL INFORMATION

Remove the Snap Caps from the license plate frame by pushing them out from the backside of the mounting hole. Caps can also be removed from the front using a small standard screwdriver. Place the clear lens face down on a soft towel or cloth. Set the rubber gasket into place and insert the four spacers into the mounting holes of the lens. Position the license plate frame face down on the gasket in the recessed area. Make certain the lip of the gasket fits over the edge of the license plate for a proper seal.

NOTE: When mounting your **SEALED LICENSE PLATE FRAME** with only two screws it is recommended that you secure the opposite end with the supplied hardware. Do not over tighten the mounting screws as this can cause damage to the lens and frame. Next position the assembly on the vehicle and secure with the appropriate mounting hardware. Finish the installation by firmly pressing the Snap Caps into place over the mounting screws.

DISCLAIMER

GRIOT'S GARAGE is not responsible for any misuse of the **SEALED LICENSE PLATE FRAME** for any injury or damage incurred to any person or object related to the **SEALED LICENSE PLATE FRAME**

ANSWERS TO YOUR QUESTIONS

Should you want to order another **SEALED LICENSE PLATE FRAME**, or for a complete selection of quality GRIOT'S GARAGE products, please write or call us toll-free at 800-345-5789. You can use the Internet at www.griotsgarage.com. Reorder item number 10390.

*Have fun in your garage!**

GRIOT'S GARAGE, INC.
3333 SOUTH 38TH STREET
TACOMA, WA 98409

800-345-5789

www.griotsgarage.com