



EXHAUST MANIFOLD DRESSING

Thank you for choosing this fine product from GRIOT'S GARAGE.

USEFUL INSTRUCTIONS

When using EXHAUST MANIFOLD DRESSING, it is not necessary to remove the manifold.

1. Remove the surface rust and dirt from **cool** manifold with a wire brush.
2. Apply the EXHAUST MANIFOLD DRESSING to the entire manifold with a toothbrush, cloth or fingers. Take your time and work the EXHAUST MANIFOLD DRESSING down into the pores of the metal. Do not use too much, only enough to cover the surface. Using too much causes flaking, which can drop onto other engine parts.
3. Start your engine and let it run until the operating temperature is reached.
4. If a shine is desired, buff with a fingernail brush.
5. For best results, remove the manifold from the car and sandblast it first, then follow the above instructions.
6. Very little maintenance is required. If discoloration occurs, simply re-apply EXHAUST MANIFOLD DRESSING on that area.

GRIOT'S GARAGE EXHAUST MANIFOLD DRESSING does not burn and is non-toxic. Store it in a cool, dark place.

SAFETY INSTRUCTIONS AND DISCLAIMER

GRIOT'S GARAGE is not responsible for the misuse of EXHAUST MANIFOLD DRESSING or for any injury or damage incurred to any person or object using EXHAUST MANIFOLD DRESSING. As with any chemical, please remember to

KEEP OUT OF THE REACH OF CHILDREN.

ANSWERS TO YOUR QUESTIONS

Should you want to order more EXHAUST MANIFOLD DRESSING, or for a complete selection of quality GRIOT'S GARAGE products, please write, use the internet or call us toll-free and ask for item number 20782.

Have fun in your garage!

GRIOT'S GARAGE, INC.
3333 SOUTH 38TH STREET
TACOMA, WA 98409
800-345-5789
www.griotsgarage.com