



## FOAMING SPRAYER

Thank you for selecting this fine GRIOT'S GARAGE product. The **FOAMING SPRAYER** lays down a sea of cleaning foam quickly and easily with the pull of the trigger. Fill the large, 32 ounce reservoir with any of our cleaners and start washing. A built-in pistol grip nozzle features a quick-connect attachment and connects to any garden hose. When you're done scrubbing, take off the nozzle and rinse with water. Perfect for cleaning any vehicle with our **CAR WASH**, wheels with our **WHEEL CLEANER**, engines with **ENGINE CLEANER** and tires with **RUBBER CLEANER**. The **FOAMING SPRAYER** regulates the application of the cleaning solution. What could be easier? Another great cleaning tool for your car care arsenal. Enjoy the best!

### USEFUL INSTRUCTIONS

1. Start by selecting a colored tip based on your water pressure. Yellow is for high water pressure, Blue (the most common) is for average water pressure and Green is for low water pressure.
2. Remove the foamer lid and locate the opening on the underside.
3. Press the small end of the colored tip firmly into the hose barb of the inlet port.
4. Slide the suction tube over the colored tip and hose barb. Make sure the strainer screen is connected to the opposite end of the tube.
5. Fill your container with cleaning product to desired level (do not add water).  
NOTE: When using **CAR WASH** add water at a ratio of 1:1. Our **CAR WASH** will not flow through the siphon tube unless it is diluted.
6. Attach the spray nozzle to your water hose and turn on the water.
7. Connect the nozzle onto the foamer lid. You will hear the quick connect lock into place.
8. Grip and squeeze the nozzle handle to apply the cleaner as needed. It will appear as light foam or solution with bubbles and dissipate fairly quickly.
9. After foaming on cleaner, disconnect the spray nozzle from the applicator by pulling back on the quick-connect (in the opposite direction to release the nozzle).
10. Clean surface as needed and rinse thoroughly using the spray nozzle.

### TROUBLESHOOTING YOUR FOAMING SPRAYER (PROBLEM-CAUSE-REMEDY)

Problem: Nozzle does not attach to lid securely

- Cause:
- Lid not secured to nozzle
  - O-ring on lid has been damaged or missing
  - Quick-connect is dirty or damaged

Remedy:

- Press nozzle quick-connect firmly on to lid until a 'snap' is heard
- Replace O-ring
- Rinse quick-connect in water
- Inspect rubber washer on nozzle side
- Inspect white locking tips inside quick-connect



## FOAMING SPRAYER (CONT'D.)

Problem: Unit does not draw cleaning concentrate

- Cause:
- Clogged suction tube
  - Metering tip obstructed
  - Water pressure too low
  - Mineral deposits in barrel of foamer lid

Remedy:

- Clean or replace
- Rinse tip or replace (altering tip opening size will change application rate)
- Minimum 25 PSI required
- Back flush unit. Remove the reservoir, suction tube and metering tip. Put finger over the main spray outlet barrel opening. Apply minimal water pressure through garden hose at nozzle of barrel to be flushed.

Problem: Weak foaming action

- Cause:
- Clogged water inlet on nozzle
  - Water pressure too low
  - Water temperature too high

Remedy:

- Clean or replace strainer
- Minimum of 25 PSI is needed for the foamer to operate
- Use lower the temperature of the water source.

If above steps fail to produce good concentrate draw and/or foaming action, contact GRIOT'S GARAGE Customer Service at 1-800-345-5789.

### DISCLAIMER

GRIOT'S GARAGE is not responsible for any misuse of the **FOAMING SPRAYER** for any injury or damage incurred to any person or object related to the **FOAMING SPRAYER**.

### ANSWERS TO YOUR QUESTIONS

Should you want to order another **FOAMING SPRAYER** or for a complete selection of quality GRIOT'S GARAGE products, please write or call us toll-free at 800-345-5789. Or visit our website: [www.griotsgarage.com](http://www.griotsgarage.com). Reorder item number 51140.

*Have fun in your garage!®*

GRIOT'S GARAGE, INC.  
3500-A 20TH STREET E.  
TACOMA, WA 98424

**800-345-5789**

**[www.griotsgarage.com](http://www.griotsgarage.com)**

© GRIOT'S GARAGE, INC.