



PAINT SAVING CLEAR PROTECTIVE SHIELD

Thank you for choosing this fine product from GRIOT'S GARAGE. The PROTECTIVE SHIELD is great for protecting painted areas that are more prone to chips and scratches. It also contains additional UV inhibitors and will minimize any paint work color variation between the protected and unprotected surfaces. Use it on front ends, around tire wells, inside door jams, along door edges, door sills, painted bumpers or any painted surface you wish to protect.

IMPORTANT PREPARATION INSTRUCTIONS

Thoroughly clean the surface to which the PROTECTIVE SHIELD is to be applied. Ensure that all dirt, grease or oil is cleaned off, then dry the surface with a lint free cloth. Any soap or cleaning solution left on the surface will make the adhesive cloudy and affect the apparent color of the underlying paint work. If the area has any paint treatment, it needs to be removed. Make sure your hands are clean and your tools are sharp when applying the SHIELD. Check surface condition (e.g. for flaking paint, paint chips). If you have the slightest doubt about the integrity of the paint work, **do not proceed**. The PROTECTIVE SHIELD should be handled only at the edges as fingerprints will leave a permanent impression in the adhesive. Liberal application of the POSITIONING SPRAY is important as the PROTECTIVE SHIELD has a very aggressive adhesive. The POSITIONING SPRAY allows you to position the SHIELD before it adheres to the surface. Position the SHIELD with the backing paper left on to the desired area of application and cut it to the desired length allowing at least 1/2" (13mm) over the edges. Remove the paper backing and apply the POSITIONING SPRAY liberally to the exposed adhesive side of the shield and the area on the vehicle to be treated. Remove all moisture using the GRIOT'S GARAGE TEFLON SQUEEGEE starting from the center to either the left or right side. Make sure the strokes are overlapped; this will prevent moisture and air bubbles from being trapped under the PROTECTIVE SHIELD. Repeat for the other side. Heat the installed film with a hair dryer on hot so that it reaches 85°C or 150°F. Trim the overlap of the PROTECTIVE SHIELD as needed.

WARNINGS AND CAUTIONS

Newly applied PROTECTIVE SHIELD must not be washed until 48 hours after application. Do not use a heat gun as this can do damage to both the PROTECTIVE SHIELD and the paint work on the vehicle. Do not store near heat, direct or indirect sunlight. The shelf life is one year when stored in original packaging. Do not use any soap solution with this product as the soap will make the adhesive backing change from transparent to cloudy. Always test a small area of paint work inside the hood or some other concealed area first. Polishes and cleaners with abrasives will scratch this product.

DISCLAIMER

These PROTECTIVE SHIELDS will not protect your paint from all impacts. Product warranty is valid only for the vehicle's original manufacturer's factory paint work. GRIOT'S GARAGE is not responsible for any damage to vehicle while the PROTECTIVE SHIELD is in use.

ANSWERS TO YOUR QUESTIONS

Should you want to order more PROTECTIVE SHIELD, or for a complete selection of quality GRIOT'S GARAGE products, please write, use the internet or call us toll-free at **800-345-5789**. Reorder item number 77890-2" WIDE PROTECTIVE SHIELD, 77892-4" WIDE PROTECTIVE SHIELD, 77633-1/2" WIDE PROTECTIVE SHIELD, or 77896-4oz. POSITIONING SPRAY & SQUEEGEE.

Have fun in your garage!™

GRIOT'S GARAGE, INC.
3500-A 20th Street E.
Tacoma, WA 98424

800-345-5789

www.griotsgarage.com

© GRIOT'S GARAGE, INC.

Mkt/PIF137/072199