



PNEUMATIC SIT-ON CREEPER

Thank you for choosing this fine product from GRIOT'S GARAGE.

INSTALLATION

1. Put the red metal base on its wheels on the floor.
2. Insert the large end of the chrome metal cylinder into the large hole in the base. The cylinder will insert into the base approximately 4".
Please note: Once the cylinder has been secured to the base and the seat, you cannot take it apart.
3. Place the hole on the bottom of the seat onto the top of the chrome cylinder.
4. Sit on the stool. Your weight will secure the cylinder in place.
Please note: The cylinder has a tapered fit and once it is secured to the seat, it cannot be removed.

OPERATION

To lower the seat: As you sit on the creeper, reach under the seat and slowly lift up on the handle until the desired height is reached.

To raise the seat: Lift off any weight from the seat. Reach under the seat and lift up on the handle until the desired height is reached. The seat will adjust from 14½" to 20" from the floor.

DISCLAIMER

GRIOT'S GARAGE is not responsible for any misuse of the PNEUMATIC SIT-ON CREEPER or for any injury or damage incurred to any person or object related to the PNEUMATIC SIT-ON CREEPER.

ANSWERS TO YOUR QUESTIONS

Should you want to order another PNEUMATIC SIT-ON CREEPER, or for a complete selection of quality GRIOT'S GARAGE products, please write, find us on the internet or call us toll-free. Reorder item number 92162.

*Have fun in your garage!**

GRIOT'S GARAGE, INC.
3333 SOUTH 38TH STREET
TACOMA, WA 98409
800-345-5789
www.griotsgarage.com