



Tar & Sap Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 09/20/2021

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Tar & Sap Remover

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Automotive Care Product

1.3. Supplier

Griot's Garage Inc.
3333 South 38th Street, Tacoma, WA 98409
2185 Airwest Blvd., Plainfield, IN 46168
Telephone: 800-345-5789
Fax: 888-252-2252
Email: info@griotsgarage.com
Website: www.griotsgarage.com

1.4. Emergency telephone number

Emergency number : 1-800-535-5053 in North America (USA, Canada, and Mexico)
1-352-323-3500 Outside North America

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 3	H226 Flammable liquid and vapor
Acute toxicity (oral) Category 4	H302 Harmful if swallowed
Skin corrosion/irritation Category 2	H315 Causes skin irritation
Serious eye damage/eye irritation Category 2	H319 Causes serious eye irritation
Skin sensitization Category 1	H317 May cause an allergic skin reaction
Carcinogenicity Category 2	H351 Suspected of causing cancer
Specific target organ toxicity (single exposure) Category 3	H335 May cause respiratory irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor
H302 - Harmful if swallowed
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H351 - Suspected of causing cancer

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing fume/mist/vapors/spray
P264 - Wash hands thoroughly after handling
P270 - Do not eat, drink or smoke when using this product

Tar & Sap Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P271 - Use only outdoors or in a well-ventilated area
P272 - Contaminated work clothing must not be allowed out of the workplace
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301+P312 - If swallowed: Call a poison center/doctor if you feel unwell
P302+P352 - If on skin: Wash with plenty of water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P330 - Rinse mouth
P332+P313 - If skin irritation occurs: Get medical advice/attention
P333+P313 - If rash occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P363 - Wash contaminated clothing before reuse
P370+P378 - In case of fire: Use recommended media to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Keep cool
P405 - Store locked up
P501 - Dispose of contents/container in accordance with local, state, and federal regulations

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Petroleum distillates, hydrotreated light	(CAS-No.) 64742-47-8	30-60*	Flam. Liq. 3, H226 Asp. Tox. 1, H304
D-Limonene	(CAS-No.) 5989-27-5	15-40*	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Skin Sens. 1B, H317 STOT SE 3, H335
Naphtha, petroleum, hydrotreated light	(CAS-No.) 64742-49-0	7-13*	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 STOT SE 3, H336 Asp. Tox. 1, H304
Coconut diethanolamide	(CAS-No.) 68603-42-9	3-7*	Carc. 2, H351
Isopropyl alcohol	(CAS-No.) 67-63-0	0.1-1*	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Diethanolamine	(CAS-No.) 111-42-2	0.1-1*	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Carc. 2, H351 STOT RE 2, H373

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/take off contaminated clothing immediately. If skin irritation or rash occurs: Get medical advice/attention.

Tar & Sap Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- | | |
|--------------------------------------|--|
| First-aid measures after eye contact | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion | : Rinse mouth. Call a poison center/doctor if you feel unwell. |

4.2. Most important symptoms and effects (acute and delayed)

- | | |
|--------------------------------------|--|
| Symptoms/injuries after inhalation | : May cause respiratory irritation. |
| Symptoms/injuries after skin contact | : Irritation. May cause an allergic skin reaction. |
| Symptoms/injuries after eye contact | : Eye irritation. |

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- | | |
|------------------------------|--|
| Suitable extinguishing media | : Water spray. Dry powder. Foam. Carbon dioxide. |
|------------------------------|--|

5.2. Specific hazards arising from the chemical

- | | |
|--|--------------------------------|
| Fire hazard | : Flammable liquid and vapor. |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released. |

5.3. Special protective equipment and precautions for fire-fighters

- | | |
|--------------------------------|--|
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |
|--------------------------------|--|

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- | | |
|----------------------|---|
| Emergency procedures | : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume/mist/vapors/spray. Avoid contact with skin and eyes. |
|----------------------|---|

6.1.2. For emergency responders

- | | |
|----------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
|----------------------|---|

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- | | |
|-------------------------|--|
| Methods for cleaning up | : Clean up liquid spill with absorbent material. Notify authorities if product enters sewers or public waters. |
| Other information | : Dispose of materials or solid residues in accordance with local, state, and federal regulations. |

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-------------------------------|---|
| Precautions for safe handling | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid breathing fume/mist/vapors/spray. Avoid contact with skin and eyes. |
| Hygiene measures | : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |

7.2. Conditions for safe storage, including any incompatibilities

- | | |
|--------------------|--|
| Technical measures | : Ground/bond container and receiving equipment. |
| Storage conditions | : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. |

Tar & Sap Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Tar & Sap Remover	
No additional information available	
Petroleum distillates, hydrotreated light (64742-47-8)	
No additional information available	
Naphtha, petroleum, hydrotreated light (64742-49-0)	
No additional information available	
D-Limonene (5989-27-5)	
USA - AIHA - Occupational Exposure Limits	
WEEL TWA (ppm)	30 ppm
Coconut diethanolamide (68603-42-9)	
No additional information available	
Diethanolamine (111-42-2)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (mg/m ³)	1 mg/m ³ (inhalable fraction and vapor)
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA) (mg/m ³)	15 mg/m ³
NIOSH REL (TWA) (ppm)	3 ppm
Isopropyl alcohol (67-63-0)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (ppm)	200 ppm
ACGIH STEL (ppm)	400 ppm
USA - ACGIH - Biological Exposure Indices	
Biological Exposure Indices (BEI)	40 mg/l (Medium: urine - Time: end of shift at end of workweek - Parameter: Acetone (background, nonspecific))
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
OSHA PEL (TWA) (ppm)	400 ppm
USA - IDLH - Occupational Exposure Limits	
US IDLH (ppm)	2000 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA) (mg/m ³)	980 mg/m ³
NIOSH REL (TWA) (ppm)	400 ppm
NIOSH REL (STEL) (mg/m ³)	1225 mg/m ³
NIOSH REL (STEL) (ppm)	500 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure adequate ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Not required under normal conditions. If concentrations exceed exposure limits, use NIOSH approved respirator.

Tar & Sap Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear
Color	: Yellow-Green
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 96 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Density (lbs./gal)	: 6.7
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

ATE US (oral)	1914.701 mg/kg body weight
Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg

Tar & Sap Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.2 mg/l/4h
Naphtha, petroleum, hydrotreated light (64742-49-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (ppm)	73680 ppm/4h
D-Limonene (5989-27-5)	
LD50 oral rat	4400 mg/kg
LD50 dermal rabbit	> 5 g/kg
Coconut diethanolamide (68603-42-9)	
LD50 oral rat	12400 mg/kg
Diethanolamine (111-42-2)	
LD50 oral rat	0.62 ml/kg
Isopropyl alcohol (67-63-0)	
LD50 oral rat	4396 mg/kg
LD50 dermal rabbit	12800 mg/kg
LC50 inhalation rat (ppm)	16000 ppm (Exposure time: 8 h)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
D-Limonene (5989-27-5)	
IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity
Coconut diethanolamide (68603-42-9)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes
Diethanolamine (111-42-2)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes
Isopropyl alcohol (67-63-0)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause respiratory irritation.
Naphtha, petroleum, hydrotreated light (64742-49-0)	
Specific target organ toxicity – single exposure	May cause drowsiness or dizziness.
D-Limonene (5989-27-5)	
Specific target organ toxicity – single exposure	May cause respiratory irritation.
Isopropyl alcohol (67-63-0)	
Specific target organ toxicity – single exposure	May cause drowsiness or dizziness.
Specific target organ toxicity – repeated exposure	: Not classified
Diethanolamine (111-42-2)	
Specific target organ toxicity – repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Tar & Sap Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
-------------------	--

Petroleum distillates, hydrotreated light (64742-47-8)

LC50 fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

D-Limonene (5989-27-5)

LC50 fish 1	0.619 – 0.796 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)

Coconut diethanolamide (68603-42-9)

LC50 fish 1	3.6 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
-------------	---

Diethanolamine (111-42-2)

LC50 fish 1	4460 – 4980 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	55 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	1200 – 1580 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

Isopropyl alcohol (67-63-0)

LC50 fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	> 1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
LC50 fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 other aquatic organisms 2	> 1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)

12.2. Persistence and degradability

Petroleum distillates, hydrotreated light (64742-47-8)

Persistence and degradability	Not established.
-------------------------------	------------------

Isopropyl alcohol (67-63-0)

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

Petroleum distillates, hydrotreated light (64742-47-8)

BCF fish 1	61 – 159
Bioaccumulative potential	Not established.

Diethanolamine (111-42-2)

BCF fish 1	(no significant bioconcentration)
Partition coefficient n-octanol/water (Log Pow)	-2.18 (at 25 °C)

Isopropyl alcohol (67-63-0)

Partition coefficient n-octanol/water (Log Pow)	0.05 (at 25 °C)
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

Tar & Sap Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Disposal methods

- Waste treatment methods : Dispose of contents/container in accordance with local, state, and federal regulations.
- Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

- Proper Shipping Name (DOT) : UN 1993 Flammable Liquid, N.O.S., (Petroleum distillates, hydrotreated light; D-Limonene), 3, PG III
- Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Packing group (DOT) : III - Minor Danger
- Hazard labels (DOT) : 3 - Flammable liquid



- Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Tar & Sap Remover	
SARA Section 311/312 Hazard Classes	Acute Toxicity Carcinogenicity Flammable Liquid Skin Irritation Serious Eye Damage or Irritation Respiratory Irritation or Sensitization Specific Target Organ Toxicity
Petroleum distillates, hydrotreated light (64742-47-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Naphtha, petroleum, hydrotreated light (64742-49-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
D-Limonene (5989-27-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Coconut diethanolamide (68603-42-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Diethanolamine (111-42-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	

Tar & Sap Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Isopropyl alcohol (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on United States SARA Section 313

EPA TSCA Regulatory Flag

T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

15.2. International regulations

CANADA

Petroleum distillates, hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

Naphtha, petroleum, hydrotreated light (64742-49-0)

Listed on the Canadian DSL (Domestic Substances List)

D-Limonene (5989-27-5)

Listed on the Canadian DSL (Domestic Substances List)

Coconut diethanolamide (68603-42-9)

Listed on the Canadian DSL (Domestic Substances List)

Diethanolamine (111-42-2)

Listed on the Canadian DSL (Domestic Substances List)

Isopropyl alcohol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Petroleum distillates, hydrotreated light (64742-47-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Naphtha, petroleum, hydrotreated light (64742-49-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

D-Limonene (5989-27-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Coconut diethanolamide (68603-42-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Diethanolamine (111-42-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Isopropyl alcohol (67-63-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Petroleum distillates, hydrotreated light (64742-47-8)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Naphtha, petroleum, hydrotreated light (64742-49-0)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on INSQ (Mexican national Inventory of Chemical Substances)

Listed on Turkish inventory of chemical

D-Limonene (5989-27-5)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Tar & Sap Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Coconut diethanolamide (68603-42-9)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican national Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

Diethanolamine (111-42-2)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Isopropyl alcohol (67-63-0)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

15.3. US State regulations

 **WARNING:** This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

SDS US (GHS HazCom 2012)

The data presented here relates only to the specific material designated herein and does not relate to use in combination with any other materials or in any process. The information set forth above is based on technical data believed to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside our control, no warranties, expressed or implied are made, and no liability is assumed in connection with any use of this information. Judgments as to the suitability of this information for the user's purposes are necessarily the user's responsibility. Although reasonable care has been taken in the preparation of this information, no responsibility is assumed as to the accuracy or suitability of this information for its application to the user's intended purpose or for consequences of its use.