



## TWIN TUBE FLUORESCENT LIGHT

Thank you for choosing this quality product from GRIOT'S GARAGE.

### **OPERATION AND RELAMPING INSTRUCTION**

Plug into any 110-125 V standard wall outlet. Depress the switch in the handle to turn the light on.

Unplug before relamping. Remove the two (2) screws in the back of the handle and remove the handle by separating the two halves. The lamp can now slide out of the tube. Remove the two wires from the old lamp by simply pulling on the white nylon connector covers. Push these same wires on the brass pins of the new lamp. Slide the new lamp into the tube, making sure that the top of the lamp sits into the white nylon pocket near the hook end of the light. Assemble the handle back onto the unit exactly as it was before disassembled. Replace and tighten the screws.

### **REPLACEMENT LAMPS AND ELECTRICAL RATING**

13 watt Lamp — .285 Amp, 118 V, 60Hz (Item #13021)

**Warning: During reassembly, position the wires in the handle away from the connecting posts to avoid pinching them.**

### **TO CLEAN OUTSIDE OF UNIT**

Unplug the unit before cleaning, and dry thoroughly before plugging the unit back into an outlet. Using a soft, damp cloth (a mild soap may be used if needed), clean the outside of the handle, tube, cord and ballast plug enclosure, being careful not to wet the electrical plug. NEVER immerse any part of the unit in water to clean. DO NOT USE solvents such as gasoline or turpentine to clean unit.

### **GENERAL SAFETY INFORMATION**

Potentially fatal electric shock hazard! Do not handle an energized fixture or energize any fixture with wet hands, when standing on a wet or damp surface, or when standing in water. This fixture must be wired in accordance with all electrical and safety codes and ordinances and the most recent National Electric Code (NEC) and Occupational Safety and Health Act (OSHA).

All wiring should be performed by a qualified electrician. Make certain that the power source conforms to the requirements of this fixture. The use of an extension cord with the fixture should be of a gauge and type that meets or exceeds code requirements. Disconnect power before installing or servicing. If the power disconnect switch is out of sight, lock it in the open position and tag it to prevent an unexpected application of power.

### **POTENTIAL FATAL ELECTRIC SHOCK HAZARD**

This equipment is only for use on 110-125V (single phase) outlets and is equipped with an approved 3 prong plug. To reduce the risk of electric shock, it should be plugged fully into a receptacle.

(Please turn sheet over)



Where a 2 prong wall receptacle is encountered, it must be replaced with a properly grounded 3 prong receptacle installed in accordance with National Electric Code, local codes and ordinances. To ensure a proper ground, the grounding means must be tested by a qualified electrician.

This fixture is intended to be used for general indoor lighting. It is not intended for use in potentially dangerous locations such as flammable or explosive atmospheres. Do not use near flammable liquids such as gasoline or turpentine or where explosion proof lamps are required. Always hang lamp over work. Do not use under vehicles as flammable liquids may drip on the handlamp. The lamp should not be used within 18" of the floor in garages.

This unit is not waterproof and is not intended to be used in showers, saunas, or in potentially wet locations. Keep this lamp away from sinks, tubs, showers, etc. Retrieving appliances when they fall into water, when plugged in, can be fatal. Disconnect the lamp from power supply before servicing or inspecting it for any reason.

The mounting device is designed specifically for wall mountings. If mounting from a ceiling is preferred, be sure to use the eyehook screw. Whether hanging from a wall or ceiling, make sure to mount into a solid framing member (e.g. rafter), **not** just drywall.

### **DISCLAIMER**

GRIOT'S GARAGE is not responsible for the misuse of the TWIN TUBE FLUORESCENT LIGHT or for any injury or damage incurred to any person or object related to the TWIN TUBE FLUORESCENT LIGHT.

### **ANSWERS TO YOUR QUESTIONS**

Should you want to order another TWIN TUBE FLUORESCENT LIGHT, or for a complete selection of quality GRIOT'S GARAGE products, please write, use the internet or call us toll-free. Reorder item numbers: TWIN TUBE CORD—13015, TWIN TUBE REEL—13020, TWIN TUBE LIGHT REPLACEMENT LAMP—13021.

*Have fun in your garage!*

GRIOT'S GARAGE, INC.  
3333 SOUTH 38<sup>TH</sup> STREET  
TACOMA, WA 98409  
**800-345-5789**  
**[www.griotsgarage.com](http://www.griotsgarage.com)**

© GRIOT'S GARAGE, INC.